

## TURBOVAC TRAY SEALERS:

LOW INVESTMENT, EASY PROGRAMMING  
AND VERY FLEXIBLE...

**Perfect for restaurants, hospitality branch, food stalls and caterers.**

The Turbovac TPS tray sealing machines are designed for packing food products under MAP-conditions. Low investment, easy programming and flexibility explain the popularity of these machines. The mould sets can be easily changed without the need of tools because of the unique "easy mould change system". The fully automatic sensor controls vacuum and gas injection to create the perfect atmosphere inside the package.

"FLEXIBLE & EASY TO USE"



TRAY SEALER TPS XL



TRAY SEALER TPS MINI



TRAY SEALER TPS MICRO

### SPECIFICATIONS TRAY SEALERS

	MACHINE DIMENSION	WORK HEIGHT	PUMP	CYCLE TIME	VOLTAGE*	POWER CONSUMPTION	AIR PRESSURE REQUIRED	WEIGHT
<b>TPS XL</b>	580 x 730 x 1300	850	21 m <sup>3</sup>	25-30 sec	400V-3-50 Hz	1,5 kW	6bar -20 ltr p. min	150 kg
<b>TPS MINI</b>	380 x 640 x 670	table top	8 m <sup>3</sup>	25-30 sec	400V-3-50 Hz	0,45 kW	6bar -20 ltr p. min	50 kg
<b>TPS MICRO</b>	500 x 580 x 660	table top	x	10 sec	230V-1-50/60 Hz	0,3 kW	x	30 kg

  

	MAX DIMENSION TRAY	MAX HEIGHT TRAY	MAX WIDTH FILM	MAX DIAMETER FILM ROLL	CORE DIAMETER FILM ROLL
<b>TPS XL</b>	395 x 290	120	400	250	any dimension
<b>TPS MINI</b>	366 x 180	50	265	250	any dimension
<b>TPS MICRO</b>	340 x 270	100	350	250	any dimension

Dimensions in mm \*Machines can be supplied with all worldwide voltages applicable

### MAXIMUM TRAY DIMENSIONS

MOULD CONFIGURATION	TPS MICRO (LXDxH)	TPS MINI (LXDxH)	TPS XL (LXDxH)	
1:1	340 x 270 x 100	265 x 180 x 90	395 x 290 x 120	
1:2	170 x 270 x 100	180 x 120 x 90	195 x 290 x 120	
2:1	x	265 x 80 x 90	395 x 140 x 120	
2:2	170 x 135 x 100	180 x 80 x 90	195 x 140 x 120	
1 x round	x	Ø 165 x 90	Ø 290 x 120	
2 x round	x	Ø 120 x 90	Ø 195 x 120	

Dimensions in mm

### OPTIONS TPS XL

- > 40 m<sup>3</sup> Vacuum pump
- > 21 m<sup>3</sup> Oxygen protected vacuum pump
- > Compressor
- > Film rewinding system
- > Liquid filter
- > Side table set